



CustomSound

| CS1000 Universal Loudspeaker | CS500 Universal Loudspeaker |
|---|---|
| 45-23,000Hz 59-20,000Hz | 65-23,000Hz 65-10,000Hz |
| 40Hz | 50Hz |
| 86dB 88dB | 85dB 87dB |
| 8 Ohms 6 Ohms | 8 Ohms 6 Ohms |
| 20 - 150 Watts 150 Watts | 20 - 120 Watts 120 Watts |
| 1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet | 1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet |
| 6 1/2" (165mm) Clay/Ceramic filled Polypropylene Cone, Rubber Surround | 5 1/4" (135mm) Clay/Ceramic filled Polypropylene Cone, Rubber Surround |
| 2,200Hz, LR4 | 1,800Hz, LR4 |
| 0.3 cu ft (8.5L) | 0.2 cu ft (5L) |
| Bass Reflex | Sealed |
| 9 1/4 x 12 1/4 x 11 3/4" 235 x 310 x 296mm | 7 5/8 x 10 1/2 x 8" 192 x 266 x 203mm |
| 10lbs (4.5kg)/each 24lbs (11kg)/pair | 5.7lbs (2.59kg)/each 16.5lbs (7.5kg)/pair |
| Black or White | Black or White |

All specifications are subject to change without notice. Non-metric measurements are approximate. PSB Speakers will not assume any liability for errors in this brochure which may result in errors being made by retailers, custom installers, cabinet makers or other end users based on information contained in this document. PSB Speakers reserves the right to change specifications or features without notice. © 2011 PSB Speakers, a division of Lenbrook Industries Limited. PSB is a registered trademark of Lenbrook Industries Limited. All rights reserved. No part of this publication may be reproduced, stored or transmitted in any form whatsoever without the written permission of PSB Speakers. Printed April 2011 * Please allow minimum 3" / 75mm for cord clearance.